



INSTALLATION INSTRUCTIONS

Part Number: VF3004

This filter fits:

SEE CATALOG FOR CURRENT APPLICATIONS

* FREE K&N® decal To register your warranty, please see us online at knfilters.com/register. FREE K&N® decal *

K&N® Cabin Air Filters replace your vehicle's stock cabin filter with a reusable design that cleans and freshens incoming air. They are electrostatically charged to grab and hold dust particles. K&N® cabin air filters help control odors while they help capture most mold, mildew, fungus, spores, bacteria and germs. When they get dirty they can be cleaned and reused and best of all, they come with a 10 year/100,000 mile limited warranty.

When applicable, refer to owner's manual for manufactures installation/removal instructions. The following are helpful steps when replacing/servicing cabin air filter with K&N® cabin air filter.

1. Remove passenger side threshold panel and kick panel.
NOTE: Unscrew plastic screw to remove kick panel. Fig. 1,2&3
2. Open glove box compartment. Locate glove box stop features. In most vehicles these are located on the left and right side of the glove box. Fig. 4
3. Remove fasteners holding stop features. Fig. 5
4. Close glove box. Locate and remove the two screws that are located under the left and right side of glove box. Fig.6&7
5. After the two screws are taken off, unlatch the glove box and remove.
6. If the cabin filter has not been serviced there will be a plastic bridge that will need to be removed to access metal crossbar. Use guides on the left and right side of plastic bridge to cut. Note: Plastic bridge will not be reused. Fig. 8
7. Remove left and right side fasteners from metal crossbar. Fig. 9&10
8. Once crossbar is loose, lower the right side to access cabin housing.
9. Locate cabin filter housing and remove cover.
10. Remove dirty cabin filters. Remove any debris that might be present on the cabin filter or in housing. Fig.11
11. Install K&N® Cabin Filter. K&N® Cabin Filter will only fit one direction. Fig.12
12. Reverse steps 1-9 to complete cabin filter installation. With the cabin filter installed, clean an area on the housing and apply the K&N® Stop Decal. The decal will help notify others that this is a reusable cabin filter.



Fig. 1




Fig. 2



Fig. 3




Fig. 4



Fig. 5



Fig. 6




Fig. 7



Fig. 8



Fig. 9




Fig. 10



Fig. 11



Fig. 12

Please visit our website knfilters.com for a complete listing of other K&N® products for your vehicle, such as oil filters, air filters, and intake kits. We recommend refreshing your K&N® Cabin Air Filter every 12 months, or 12,000 miles. Use K&N® Refresher kit pt.# 99-6000 which includes the easy to follow instructions.