

MSDS K&N Air Filter Oil Aerosol  
99-0504EU, 99-0506EU, 99-0516EU, 99-5000EU, 99-5003EU

## **K&N FILTER OIL**

### **1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** K&N FILTER OIL AEROSOL  
**Use/description of product:** Aerosol. Extremely flammable.  
**Product Code:** 04080/16/240  
**Revision Date:** 16/12/2009  
**Company Name:** ROCK OIL,  
 90 PRIESTLEY STREET  
 WARRINGTON  
 CHESHIRE  
 WA5 1ST  
**Day time tel No.** +44-1925-636191  
**Emergency Telephone No:** +44-1925-636191  
**Fax:** +44-1925-632499  
**e-mail:** [sales@rockoil.co.uk](mailto:sales@rockoil.co.uk)

### **2. HAZARDS IDENTIFICATION**

**Main hazards:** Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

### **3. COMPOSITION / INFORMATION ON INGREDIENTS**

**Ingredients:** LOW BOILING POINT MODIFIED NAPHTHA-NAPHTHA(PETROLEUM) SOLVENT REFINED

LIGHT 1-10%

CAS: 64741-84-0

EINECS: 265-086-6

[F] R11; [Xi] R38; [N] R51/53; [Xn] R65; [-] R67;

BUTANE 1-10%

CAS: 106-97-8

EINECS: 203-448-7

[F+] R12;

### **4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. Corneal burns may occur.

**Ingestion:** Nausea and stomach pain may occur. There may be vomiting and diarrhoea. There may be loss of consciousness. Convulsions may occur.

**Inhalation:** Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath. There may be loss of consciousness. Convulsions may occur.

### **4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Do not induce vomiting. If conscious, give 1 pint of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place

MSDS K&N Air Filter Oil Aerosol  
99-0504EU, 99-0506EU, 99-0516EU, 99-5000EU, 99-5003EU

in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide. Alcohol resistant foam.

**Exposure hazards:** Extremely flammable. Vapour may travel considerable distance to source of ignition and flash back. Forms explosive air-vapour mixture.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Eliminate all sources of ignition. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Mix with sand or vermiculite. Wash the spillage site with large amounts of water.

## 7. HANDLING AND STORAGE

**Handling requirements:** Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance. Smoking is forbidden.

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed. Ensure lighting and electrical equipment are not a source of ignition.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety goggles.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck. Boots made of PVC.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>State:</b>	Aerosol
<b>Colour:</b>	Dark red
<b>Odour:</b>	Perceptible odour
<b>Evaporation rate:</b>	Moderate
<b>Solubility in water:</b>	Insoluble
<b>Flash point °C:</b>	-40

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Sources of ignition. Flames.

**Materials to avoid:** Oxidising agents.

## 11. TOXICOLOGICAL INFORMATION

**Ingredients:** LOW BOILING POINT MODIFIED NAPHTHA-NAPHTHA(PETROLEUM) SOLVENT  
REFINED  
LIGHT

## 12. ECOLOGICAL INFORMATION

**Ingredients:** LOW BOILING POINT MODIFIED NAPHTHA-NAPHTHA(PETROLEUM) SOLVENT  
REFINED  
LIGHT//eco

**Mobility:** Insoluble in water. Readily absorbed into soil.

**Persistence and degradability:** Not biodegradable.

**Other adverse effects:** Harmful to aquatic organisms.

MSDS K&N Air Filter Oil Aerosol  
99-0504EU, 99-0506EU, 99-0516EU, 99-5000EU, 99-5003EU

### 13. DISPOSAL CONSIDERATIONS

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

### 14. TRANSPORT INFORMATION

**ADR / RID**

**UN no:** 1950 **ADR Class:** 2

**Labelling:** 2.1

**Shipping name:** AEROSOLS

**IMDG / IMO**

**UN no:** 1950 **Class:** 2

**EmS:** 2-13 **Marine pollutant:** .

**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950 **Class:** 2

**Labelling:** 2.1



### 15. REGULATORY INFORMATION

**Hazard symbols:**

Extremely flammable.



**Risk phrases:**

R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Safety phrases:**

S2: Keep out of the reach of children

S23: Do not breathe aerosol.

S46: If swallowed, seek medical advice immediately and show this container or label

S51: Use only in well-ventilated areas.

**Precautionary phrases:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

### 16. ADDITIONAL INFORMATION

**Risk phrases used in s.2:**

R12: Extremely flammable.

R38: Irritating to skin.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R67: Vapours may cause drowsiness and dizziness.

R12: Extremely flammable.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.